

面Bと取付穴寸法は同じ
Installation hole dimensions
same as surface B

面Bと取付穴寸法は同じ
Installation hole dimensions
same as surface B

面B surface B

SMコネクタ_Connector 3P
①:茶_Brown(+)
②:NC
③:青_Blue(-)


(30)ナットスロット使用範囲
Nut slot range of use

照射面側_Irradiation side


4 x M3 ナットスロット
Nut slot

4 x M4
(取付用_For installation)

面Bと取付穴寸法は同じ
Installation hole dimensions
same as surface B



A-A
(2 : 1)



M3ナットスロット詳細図
_Nut slot Detail drawing

型式_Model name	消費電力_Power consumption
LFX3-50RD-PT-A	13W
LFX3-50RD-PT-B	
LFX3-50SW-PT-A	12W
LFX3-50SW-PT-B	
LFX3-50BL-PT-A	6.1W
LFX3-50BL-PT-B	
LFX3-50IR860-PT-A	6.6W
LFX3-50IR860-PT-B	

	LFX3-50□□-PT-A	LFX3-50□□-PT-B
導光板パターン幅 Light guide plate pattern width	1mm	2mm

入力電圧_Input Voltage : DC 24V
消費電力_Power Consumption : 表参照_Table reference

UNIT:mm

REVISION	DATE	DESCRIPTION	REVISED
000			

ISSUE DATE	SCALE	APPROVED	NAME
2016/03/07	1:1	Y.SHIKANO	LFX3-50□□-PT-A/LFX3-50□□-PT-B
		CHECKED	DRAWING NAME
		T.OSAWA	外観図_Outline
		DESIGNED	
	A3	PROJECTION	DRAWING No.
		N.KANI	REVISION
		DRAWN	01
		N.KANI	000
			01

CCS Inc.